



### EUROCEL PROFIL 770

#### Short description:

Double sided adhesive foam tape

#### Product Data

<b>Backing:</b>	Crosslinked black PE foam, 0.8 mm
<b>Adhesive:</b>	acrylic
<b>Liner:</b>	double sided green siliconized PE film
<b>Total thickness (without liner)</b>	0.850 mm
<b>Adhesion to steel</b>	o.s. 14 N/25mm c.s. 14 N/25mm
<b>Tensile strength MD</b>	24 N/25mm
<b>Elongation at break</b>	220 %
<b>Temp. Resistance</b>	90 °C

#### Application

Double sided black PE foam tape, designed for fixing decoration profiles, plates, etc. in the field of car repair.

Features	Benefits
Acrylic adhesive	<ul style="list-style-type: none"><li>➤ High adhesion</li><li>➤ Well performing on uneven surfaces</li><li>➤ Excellent resistance to UV, atmospheric agents and ageing</li></ul>
Black PE foam backing	<ul style="list-style-type: none"><li>➤ High elongation</li><li>➤ Excellently conformable</li><li>➤ Hand tearable</li><li>➤ Easy to use</li></ul>

*Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.*

SICAD S.p.A., Via Caduti della Liberazione, 57 21040 Uboldo (VA) - ITALY  
Tel.+39 02 96412.1; Fax +39 02 96412322 export market; Fax +39 02 96780832 domestic market;  
E-mail: info@eurocel.it - www.eurocel.it - www.sicadgroup.com

This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss