



Shrub / Stain Cover 500 ml (V500COPRI)

Before painting your wall surfaces, prepare them to last: this Ambro-Sol spray can covers and defends the walls from a lot of stains. Super fast drying!

STAIN COVER - It's a formulate that gives high hiding power after just one coat to completely eliminate any stain at all by penetrating deep below the surface and then creating a seal for the prevention of new stains. Suitable for all stains caused by smoke on walls, mildew, and dirt in general. The STAIN COVER covers any stain when applied evenly over the area to be treated. The removal of particularly "resistant" stains may require repeated application of product always from a distance of 20-30 cm, paying attention to avoid runs. The product dries in 5-8 minutes if applied at a temperature of 20°C.

Technical Specifications:



Product subject to directive C.O.V.
Subcategory: Special finishes
Limit value COV: 840 g/Liter

Quantity	500 ml
Box / Case	12 Pcs
Aspect	Tin-Plate can containing under pressure fluid
Chemical nature	Quick drying acrylic paints
Colour	White
Odour	Characteristic of solvent
Relative density at 20°C	0,77 ÷ 0,81 g/ml Primer e Antirust
Flash point	Und. 0° C extremely flammable
Writing on spray bottom	Barcode, Batch date, product name
Pressure	at 20°C 5,5 ± 0,5 bar
Viscosity Ford cup	from 13" to 18"
Dry residual in spray	46% (on dry film)
Gloss	From 5 to 10 Gloss (Glossmeter angle 60°)
Thickness 1 coat	13-24 Micron
Thickness 3 coats	36-54 Micron
Resistance temperature	-10°C / +130°C (Peak 150° C)
Drying time t=20°:	Out dust: 8-10 minutes Dry to touch: 30 minutes Dry in full depth: 22 hours Overcoating Interval: 22/48 hours
It is possible to have different type of dispenser for various effects and employ	

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT

HOW TO USE: The surface must be completely dry. Shake the spray vigorously at least for 1 minute, until you feel the balls move freely. It is also advisable to occasionally shake the spray even during the use. Test in a hidden area to check its compatibility with the support to be painted. Apply a light first coat to improve coverage and adhesion to avoid the possibility of dropping. The application distance is about 20 cm; after a few moments apply a second horizontal coat immediately followed by a third vertical coat; let it dry for a few minutes; after use, it is advisable to spray for 2/3 seconds with the spray can upside down, to prevent the block of nozzle. Particularly indicated on white walls.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.